




## TeSys Deca - auxiliary contact - 2 NO

GVAE20



M	a	ır	1
---	---	----	---

Width

Range	TeSys TeSys Deca	
Device short name	GVAE	
Product or component type	Auxiliary contact block	
Product compatibility	GV2L GV3P GV2ME LS1D32 GV3L GV2RT GV2P GV2LE	
Mounting location	Front side	
Pole contact composition	2 NO	<b>X</b> /
Quantity per set	Set of 10	

Complementary		
[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 250 V conforming to IEC 60947-1	
[Ue] rated operational voltage	24240 V AC 2460 V DC	
[Ith] conventional free air thermal current	2.5 A	
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles	
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles	
Tightening torque	1.4 N.m - on screw clamp terminals	
Height	11 mm	

45 mm

Depth	29 mm
Net weight	0.02 kg
Environment	
Environmental characteristic	Normal environment
Product certifications	UKCA
Daakina Unita	
Packing Units Unit Type of Package 1	PCE /
Number of Units in Package 1	1
Package 1 Weight	19.0 g
Package 1 Height	1.6 cm
	5 cm
Package 1 width	
Package 1 Length	6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	209.0 g
Package 2 Height	6.3 cm
Package 2 width	7.3 cm
Package 2 Length	12 cm
Unit Type of Package 3	S02
Number of Units in Package 3	220
Package 3 Weight	4.377 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and
	never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

18 months



Connections and Schema



