

Product datasheet کلیک کنید

Specifications



High power contactor, TeSys Giga, 3 pole (3NO), AC-3 $\leq 440\text{V}$ 800A, standard version, 100...250V wide band AC/DC coil

LC1G800KUE

Main

Range	TeSys
Range Of Produc	TeSys Giga
Product Or Component Type	Contactors
Device Short Name	LC1G
Contactors Application	Power switching Motor control
Utilisation Category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8a AC-8b DC-1 DC-3 DC-5
Poles Description	3P
[Ue] Rated Operational Voltage	$\leq 1000\text{ V AC } 50/60\text{ Hz}$ $\leq 460\text{ V DC}$
[Ie] Rated Operational Current	1050 A (at $<40\text{ }^\circ\text{C}$) at $\leq 1000\text{ V AC-1}$ 800 A (at $<60\text{ }^\circ\text{C}$) at $\leq 440\text{ V AC-3}$
[Uc] Control Circuit Voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control Circuit Voltage Limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $<60\text{ }^\circ\text{C}$) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $<60\text{ }^\circ\text{C}$)

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	1050 A (at $40\text{ }^\circ\text{C}$)
Rated Breaking Capacity	5870 A at 440 V
[Icw] Rated Short-Time Withstand Current	5.5 kA - 10 s 4.6 kA - 30 s 3.6 kA - 1 min 2.6 kA - 3 min 1.7 kA - 10 min
Associated Fuse Rating	800 A aM at $\leq 440\text{ V}$ for motor 630 A aM at $\leq 690\text{ V}$ for motor 1250 A gG at $\leq 690\text{ V}$

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Average Impedance	0.000065 Ohm
[Ui] Rated Insulation Voltage	1000 V
Power Dissipation Per Pole	70 W AC-1 - lth 1050 A 42 W AC-3 - lth 800 A
Compatibility Code	LC1G
Pole Contact Composition	3 NO
Auxiliary Contact Composition	1 NO + 1 NC
Motor Power Kw	200 kW at 230 V AC 50/60 Hz (AC-3e) 335 kW at 400 V AC 50/60 Hz (AC-3e) 355 kW at 415 V AC 50/60 Hz (AC-3e) 375 kW at 440 V AC 50/60 Hz (AC-3e) 425 kW at 500 V AC 50/60 Hz (AC-3e) 560 kW at 690 V AC 50/60 Hz (AC-3e) 450 kW at 1000 V AC 50/60 Hz (AC-3e) 250 kW at 230 V AC 50/60 Hz (AC-3) 450 kW at 400 V AC 50/60 Hz (AC-3) 450 kW at 415 V AC 50/60 Hz (AC-3) 450 kW at 440 V AC 50/60 Hz (AC-3) 500 kW at 500 V AC 50/60 Hz (AC-3) 560 kW at 690 V AC 50/60 Hz (AC-3) 450 kW at 1000 V AC 50/60 Hz (AC-3) 200 kW at 230 V AC 50/60 Hz (AC-4) 375 kW at 400 V AC 50/60 Hz (AC-4) 355 kW at 415 V AC 50/60 Hz (AC-4) 375 kW at 440 V AC 50/60 Hz (AC-4) 400 kW at 500 V AC 50/60 Hz (AC-4) 475 kW at 690 V AC 50/60 Hz (AC-4) 400 kW at 1000 V AC 50/60 Hz (AC-4)
Motor Power Hp	300 hp at 200/208 V 60 Hz 350 hp at 230/240 V 60 Hz 700 hp at 460/480 V 60 Hz 800 hp at 575/600 V 60 Hz
Irms Rated Making Capacity	7640 A at 440 V
Coil Technology	Built-in bidirectional peak limiting
Mechanical Durability	5 Mcycles
Inrush Power In Va (50/60 Hz, Ac)	800 VA
Inrush Power In W (Dc)	680 W
Hold-In Power Consumption In Va (50/60 Hz, Ac)	15.0 VA
Hold-In Power Consumption In W (Dc)	9.5 W
Operating Time	40...70 ms closing 15...50 ms opening
Maximum Operating Rate	600 cyc/h AC-3 600 cyc/h AC-3e 300 cyc/h AC-1 150 cyc/h AC-4
Connections - Terminals	Power circuit: bar 2 - busbar cross section: 52 x 20 mm Power circuit: lugs-ring terminals 1 185 mm ² Power circuit: bolted connection Control circuit: push-in 1 0.2...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm ² with cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: flexible with cable end
Connection Pitch	70 mm
Mounting Support	Plate

Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme CCC cULus EAC CE UKCA EU-RO-MR by DNV-GL
Tightening Torque	58 N.m
Height	284 mm
Width	211 mm
Depth	266 mm
Net Weight	14.2 kg

Environment

Ip Degree Of Protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-60...80 °C
Mechanical Robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective Treatment	TH
Permissible Ambient Air Temperature Around The Device	-40...70 °C at Uc

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	34.500 cm
Package 1 Length	60.500 cm
Package 1 Weight	16.416 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	2
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	42.832 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information Yes

✓ Pvc Free

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

Installation

Installation Videos

[TeSys Giga - How to install the auxiliary contact block](#)

[TeSys Giga - How to install and remove remote wear diagnosis module](#)

[TeSys Giga - How to install mechanical interlock kit](#)

[TeSys Giga - How to install cable memory kit](#)

[TeSys Giga - How to directly mount LR9G overload relay](#)

[TeSys Giga - How to replace control module](#)

[TeSys Giga - How to replace switching modules](#)

[TeSys Giga - How to assemble reverser solution](#)

[TeSys Giga - How to assemble change-over solution](#)

