

Product data sheet

Specifications



Contactor coil, TeSys Deca, LX1D6, 220V AC 50/60Hz for 80 and 95A contactor

LX1D6M7

Product availability: Stock - Normally stocked in distribution facility

Price*: 52.32 USD

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX1D6
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	220 V AC 50/60 Hz
Average Resistance	102 Ohm 68 °F (20 °C)
Inductance Of Closed Circuit	6.7 H
Product Compatibility	LC1D40 LC1D50 LC1D65...D95
Mechanical Durability	4 Mcycles
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Drop-out: 0.3...0.6 Uc at 50/60 Hz (at <131 °F (55 °C)) Operational: 0.8...1.1 Uc at 50 Hz (at <131 °F (55 °C)) Operational: 0.85...1.1 Uc at 60 Hz (at <131 °F (55 °C))
Inrush Power In Va	245 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 245 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	26 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 26 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	6...10 W 50/60 Hz

Environment

Ambient Air Temperature For Operation	23...140 °F (-5...60 °C)
Net Weight	0.62 lb(US) (0.28 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112
Gtin	3389110233384
Returnability	Yes
Country Of Origin	CZ

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.24 in (5.700 cm)
Package 1 Width	3.74 in (9.500 cm)
Package 1 Length	4.92 in (12.500 cm)
Package 1 Weight	11.04 oz (313.000 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	16
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	11.72 lb(US) (5.318 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Reach Free Of Svhc

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

California Proposition 65 WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov